Submittal Data Model No. MSABE-24HRFN1-MT0W & MOD30-24HFN1-MT0W SINGLE ZONE MINI-SPLIT DUCTLESS SEER 20.50 24,000BTU/H HEAT PUMP

Job Name:	Location:	Date:	

Indoor

Outdoor

Capacity

Input

MSABE-24HRFN1-MT0W

MOD30-24HFN1-MT0W

208-230V~60Hz,1Ph

24000

1920

Ph-V-Hz

Btu/h

W

Purchasher: Engineer:

Submitted To: For: Review() Approval ()

Power supply





COMPATIBILITY

SINGLE ZONE INDOOR SYSTEM:

MODEL NO. MSABE-24HRFN1-MT0W

SINGLE ZONE OUTDOOR SYSTEM:

MODEL NO. MOD30-24HFN1-MT0W

SPECIFICATIONS


Accessories	Line sets – insulated	TCP24L25 TCP24L50
0.11	and flared.	D 1110
Outdoor	Wall bracket	PJ412E
Outdoor	Riser	SD01B
	support	
Safety		ETL
Certifications		
Warranty		2 YEARS PARTS,
		6 YEARS
		COMPRESSOR


Cooling	Input	VV	1920
	Rated current	Α	8.4
	EER / SEER	Btu/w	12.5 / 20.50
Heating	Capacity	Btu/h	25000
	Input	W	2315
	Rated current	Α	10.1
	COP	W/W	3.2
	HSPF4 / HSPF5	Btu/w	10 / 8.30
MAX.FUSE		А	25
Compressor	Model		ATF235D22UMT
	Туре		ROTARY
Indoor air flow (Hi/Mi/Lo)		m3/h	1050/800/550
Indoor air flow (Hi/Mi/Lo)		CFM	618/471/324
Indoor noise level (Hi/Mi/Lo)		dB(A)	47.5/42/33
	Dimension(W*D*H)	inch	42.52x8.90x13.19
Indoor unit	Packing (W*D*H)	inch	45.47x16.34x12.40
	Net/Gross weight	lbs.	29.1/37.0
Outdoor air flov	-	m3/h	4000
Outdoor air flov	ı	CFM	2355
Outdoor noise level		dB(A)	61
	Dimension(W*D*H)	inch	40.55x16.54x31.89
Outdoor unit	Packing (W*D*H)	inch	42.91x19.69x34.06
	Net/Gross weight	lbs.	136.69/147.27
Refrigerant type	9	g	R410A/2350g
Refrigerant type	9	Oz.	R410A/82.9
Refrigerant pre	-charge	Ft.	25
Additional char		Oz.	0.322
Design pressur	e	PSIG	550/340 PSIG
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Ф9.52/Ф15.9(3/8"/5/8")
	Max. refrigerant pipe length	Ft.	164
-	Max. difference in level	Ft.	82
Connection wiring		16AWG	6*4 Stranded, unshielded
Operation	Indoor(cooling/ heating)	°F	62~90/32~86
temperature	Outdoor(cooling/heating)	°F	-13~122/-13~86
Application area		Sq.ft.	330-484


Submittal Data Sheet Page 1 of 2

NORTH AMERICAN HVAC PRODUCTS LTD

Tel: 604-4308496 Fax: 1-866-9034371 www.northamericanhvac.com







GENERAL FEATURES

- * Ultra-Quiet Operation
- * Random swing, airflow direction control
- * Self-Diagnostics, LCD display
- * Auto restart operation
- * Remote control include
- * Dehumidifier mode
- * Refrigerant leakage detect
- * Local service parts stock in BC, Canada





For continual product development, North American HVAC Products Ltd reserves the right to change specifications without notice.

Submittal Data Sheet Page 2 of 2